



25189

PATENT TRADEMARK OFFICE

UTILITY APPLICATION
OF
NICHOLAS M. MIDDLETON
FOR
UNITED STATES PATENT
ON
GOLF CLUB

Docket Number: 03-12585
Sheets of Drawings: THREE (3)
Sheets of Written Description: THIRTY-ONE (31)
Express Mail Label Number: EL 987635494 US

Attorneys
CISLO & THOMAS LLP
233 Wilshire Boulevard, Suite 900
Santa Monica, California 90401-1211
Tel: (310) 451-0647
Fax: (310) 394-4477
Customer No.: 25,189
www.cislo.com

GOLF CLUB

Cross-References to Related Applications

This application is a continuation of U.S. Application Serial No. 10/112,207
5 filed March 28, 2002, which is a continuation-in-part of U.S. Application Serial No.
09/971,319 filed October 3, 2000, now U.S. Patent No. 6,435,975, which is a
continuation of U.S. Patent Application Serial No. 09/491,570 filed January 26, 2000,
now abandoned.

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to golf clubs, and more particularly although not
necessarily exclusively, to putters which are used in the game of golf to strike the ball
15 along the surface of a green.

Description of the Related Art

Golf is generally played on courses having eighteen or nine holes having "tees"
at one end of the hole from which a ball is initially struck by a player and a green
20 provided with a hole therein at the alternate end. The tee and the green are separated
by a fairway and the general principle behind the game of golf is to deposit the ball in
the hole on the green with as few strikes of the ball as possible.

Putters are typically used on the greens and on the fringes surrounding the greens to strike the golf ball towards the hole with the aim of depositing the ball in said hole. The hole is only of the order of 12 centimetres in diameter and when it is considered that putts, which term is commonly used to describe the strokes taken with a putter, may often be in excess of 12 meters (40 feet), it will be understood that great accuracy is required to ensure that the resulting position of the ball after the stroke is at least proximate if not within the hole. In general, the distance of the ball from the hole is proportional to the likelihood that the putt will be missed, i.e. further putts will be required to deposit the ball in the hole.

10

It is well known in the game of golf that a significant element of the professional game is centered on putting, and poor putters of the ball rarely achieve successful results. Indeed the difference between the scorecards of players with equal "tee to green" ability, but different putting ability is immediately evident.

15

It is surprising that there are currently relatively few putting training devices available, especially when it is considered that putting is such an essential element of the game. One device which is available, but adapted for conventionally indoor use, consists of a plastic tray provided with a U-shaped inclined channel which narrows along its length, one end of the channel being closed off and located substantially centrally and above the base of the device, the alternate end being open and adjacent the base level. The channel is typically integrally moulded into the device such that on

20

placing the device on a carpet or the like, the wider open end of the channel coincides with the periphery of the device to create a sharp lower edge which rests on the said carpet. The channel is inclined upwardly from the wider open end to the closed off end which is within the body of the device. Also within the device there is provided a
5 battery powered ejector mechanism.

In use the device is placed on a carpet, and a user wishing to practice his putting stands some distance away from the device and putts balls toward the device, which is disposed with the wider open end of the channel facing towards the user.
10 The provision of a sharp lower edge of the channel which rests on the carpet facilitates the passage of a ball accurately struck along the said carpet by the user into the channel and towards the closed off end thereof provided in the device. A ball struck by a putter with the correct weight and accuracy of direction towards the device will locate itself in the closed end of the channel, which is provided with a slight recess and moulded to the
15 spherical shape of a golf ball. The battery powered ejector mechanism then detects the presence of a ball in the closed end of the channel and ejects same back down the inclined channel towards the putter who can again attempt to putt the ball with said correct weight and direction. It can be appreciated that a good putter of the ball will be capable of repeatedly striking the ball such that it is received by the narrowing channel
20 and located in the recess at the closed end thereof.

The primary and pervasive disadvantage of such training devices is that they do not address any of the often numerous imperfections in the putting stroke of the player. In order to strike a golf ball with a putter directionally accurately, a smooth unerring swing is required. In particular, it is generally believed that the arc along which the putter head travels as the same is taken away from the stationary ball during the “backswing,” the arc which the putter head follows as it is returned to the ball to strike same, and the arc followed thereby after the ball has been struck, i.e. follow through, are to be part of the same imaginary circle whose centre is approximately between the shoulders of the golfer. Furthermore, the diameter of said circle in the direction which it is desired to strike the ball must be parallel to the plane containing the legs of the player. If this were not the case, the putting stroke of the player would either slice the ball at impact from above when viewed from above, or would push the ball from below. In any event, an undesirable component of velocity would be imparted to the ball at impact with the face. The only component of velocity ideally imparted to the ball at impact is in the desired striking direction. In this case the ball simply rolls in the direction in which it was struck.

OBJECTS OF THE INVENTION

It is an object of this invention to provide a putting device which allows a player to analyse whether he is imparting any desirable velocity components to the ball at impact.

It is a further object of this invention to provide a putter which preferably does not infringe current regulations concerning putter configurations and which therefore can be used in competition, as well as in “unofficial” games and/or practise.

5 It is a still further object of this invention to provide a putter which can be used in a variety of different ways to immediately indicate the accuracy of the putting stroke of a player.

It is yet a further object of the invention to provide a putter which when used in
10 training, enables a user to “groove” his putting stroke by ensuring that the arcuate rotational travel of the putter head conforms to the theoretical optimum described above, in particular by conforming the backswing and follow through of the player to the optimum described before and after impact respectively.

15 It is a further object of the invention to provide a training device which defocuses the mind of the user on the actual point of impact, and increases the concentration of that user on the particular arc of swing during the stroke.

These and other objects and advantages of the present invention will be apparent
20 from a review of the following specification and accompanying drawings.

SUMMARY OF THE INVENTION

According to the present invention in a first aspect there is provided a golf club including a head with at least one striking face, a rear face or edge and side faces or edges, any of which may be curved, said edges or faces defining a head of a
5 predetermined thickness, a shaft being attached to said head for use in swinging the club, said head having at least one further arcuate face or edge or further planar faces or edges defining at least one recess between the side faces or edges wherein the said at least one recess defined by said further faces or edges is adapted to receive an object or article behind the striking face of the head.

10

Typically the at least one recess passes through the thickness of the golf club head.

In one embodiment the object or article is movable with respect to the head but
15 the head acts to restrict the movement thereof in a direction parallel to the striking face when the said ball is in contact with the said further faces or edges during the swinging of the club by a user.

Typically the golf club is a putter with which the invention is particularly suited
20 and reference hereon in is made to a putter when defining the invention.

It is to be pointed out that the shaft does not comprise a key feature of the invention, and accordingly the invention in a further aspect relates to a golf club head with the features as herein described.

5 The object or article in the recess can be of any shape or size to suit the recess but a ball, and more particularly a conventional golf ball is well suited in a preferred embodiment.

10 In a first embodiment of the invention the recess opens to the rear face or edge of the putter, and in a second alternative embodiment, the recess is closed to form an aperture within the body of the putter. Preferably the aperture is circular and of a diameter marginally greater than the diameter of a conventional golf ball.

15 Preferably, the recess of the first embodiment is defined at least on two sides by the further faces or edges within the body, the separation of the said faces or edges being marginally greater than the article to be placed in the recess in use.

20 In the former embodiment, the further faces or edges are preferably substantially parallel and perpendicular to the striking face. Further preferably said further faces or edges are provided substantially equidistantly from the centre of the striking face, and accordingly can have the additional function of alignment means.

In any event the head of the putter is preferably provided with additional alignment means which allow the user of the putter to position the striking face squarely to the desired direction of travel of the ball after striking thereof.

5 Preferably additional weighting elements are provided in the body of the putter head on either side of the recess to provide a balanced “toe/heel” weight distribution. The toe and the heel of the putter head are those regions towards the extremities of the striking face and providing such a weight distribution across the striking face reduces the twisting moment imparted to the putter head on impact with the ball when the point
10 of impact is displaced from the centre of the striking face.

In one embodiment the article or object placed in the recess can be placed in a “fixed” position during use so as to provide a selected effect in use of the golf club. In one embodiment the article or object has a weight or weight distribution which
15 changes the characteristics of the club when fixed in the recess, typically via any convenient form of engagement means. The article or object may be a weight which can be moved within the aperture or recess without being released therefrom to alter the weight and moment of inertia characteristics of the club head.

20 The golf club head can be of any suitable shape such as a “mallet” or blade type head.

Preferably the putter conforms to the regulations concerning putters of the Royal and Ancient (R&A) Golf Association. In this case the putter of the present invention can be used in competitions. Other training devices are either impossible to use in competition or do not conform to the regulations of the R&A. Henceforth the
5 uniformity of putting stroke acquired during training is not immediately lost once playing on the golf course, as is so often the case with current training means employed by golf professionals.

Preferably, in the case where the recess is provided as an aperture in the putter
10 head throughout the thickness thereof is defined by the said further faces or edges, said aperture is substantially centrally located of the putter head body considered as a whole. However, different locations of the aperture may be provided depending on personal choice, or to suit particular training techniques and practices.

15 Regardless of the position of the aperture, a heel-to-toe weight distribution can automatically be achieved because the removal of mater from the body head in the manner described automatically increase the relative weights towards the extremities of the striking face.

20 It has been postulated that a larger "sweet spot" (that area of the striking face which when impacted causes resonant dynamics within the body of the putter head) can be achieved if the aperture is provided towards the rear of the putter head body.

Experimentation can define the precise location of the said aperture to give rise to the largest sweet spot, for particular head designs.

In a further embodiment of the invention, in addition to receiving an object or
5 article, the recess is provided to receive an insert in the form of a sleeve.

In one embodiment the sleeve is provided to alter the size and/or shape of the recess in which the object or article is to be placed. In addition, or alternatively, the insert is provided in the recess so that after the article or object has been placed therein
10 the insert acts to retain or improve retention of the object or article in the recess and/or further guide the movement of the object with the head.

In one embodiment the insert can be positionally moved with respect to the head and recess. In one embodiment, when an article or object is also placed in the recess
15 the insert can be moved to adjust the position of the object or article within the recess, and thereby allow a plurality of positions for the article in the recess.

Alternatively the insert is itself the selectable article or object and can be positionally moved with respect to the recess so as to cause variation in the
20 performance of the same.

In a further embodiment, the walls of the club head which define the recess are shaped to suit particular requirements and may, for example, be concave or convex shaped to retain or allow controlled release respectively of the article from the recess.

5 Typically the article is a golf ball and in one embodiment each of the recesses is provided for the reception of an article therein. The recesses can be arranged and positioned with respect to each other in any desired configuration but two particularly effective arrangements are for the plurality of recesses to be arranged along an axis substantially perpendicular to the plane of the striking face of the club head or
10 alternatively or in addition for a plurality of recesses to be arranged along an axis substantially parallel with the striking face of the club head. The arrangement of the recesses in different configurations allows different and selective attributes of a golf club swing to be monitored such as the swing arc, head accuracy in movement and/or club grip.

15

To further allow different characteristics to be selectively monitored, the recesses can be formed such that each article is released from the respective recess at different points of the golf club swing, such that the path of the released articles thereafter indicating a characteristic or characteristics of the swing at the instant of
20 release of the said article. This can be achieved by either or a combination of forming the recesses with different shaped walls and/or altering the depth of respective recesses.

In a further aspect of the invention, there is provided a golf club head having at least one striking face, a rear face or edge and side faces or edges, said edges or faces defining the club head body which further has a predetermined thickness, said head having at least one further arcuate face or edge or further planar faces or edges defining
5 at least one recess between the side faces or edges and throughout the thickness of the body, wherein the at least one recess defined by said further faces or edges is adapted to receive an object or article behind the striking face of the club head.

In one embodiment the recess is formed or receives an insert which allows an
10 article in the form of a golf ball to be picked from a surface and retained in the recess of the golf club head until released by the golf club user. In this embodiment the golf club head can be used as a means for picking up a golf ball thereby saving the user from bending down to retrieve the same and when one considers that the golf club can be used in practice where a large number of swings and golf ball releases can be
15 performed in accordance with the invention, the ability to receive and reinsert the ball in position for the next practice is useful.

In a further embodiment the recess can receive an insert which in turn is adapted to receive and locate a further training device for use with the golf club. One possible
20 device is an alignment device.

According to a third aspect of the invention there is provided an attachment for a putter head capable of being attached thereto by any suitable means, said attachment having an attachment location and at least one arcuate face or edge or further planar faces or edges defining at least one recess therebetween, said recess being defined
5 behind, in front of, or above the putter head, wherein the at least one recess is adapted to receive an object or article such as a conventional golf ball and restrict the movement thereof in a direction parallel to the striking face when the said ball is in contact with the said faces or edges during the swinging of the putter by a user.

10 Most preferably, the attachment defines a plurality of recesses, each of which may be sized to receive a conventional golf ball.

It is yet further preferable that the attachment is disposed behind the striking face of the putter head in conventional use.

15 Preferably the attachment is provided with at least one arcuate hoop behind or in front of the attachment location, the edges or faces defining same having a separation which is marginally greater than that of the diameter of a conventional golf ball.

20 In an alternative embodiment, the attachment may be provided with a pair of spaced limbs extending substantially parallel and rearwardly of the attachment location,

the separation of said limbs being marginally greater than the diameter of a conventional golf ball.

Preferably the attachment means ensures uniform and repeatable attachment to
5 the said putter head.

In the case where the putter to which the attachment is to be affixed is a mallet type putter having a mallet shaped head, the applicant foresees that the attachment may be simply mounted on the upper surface of the club head so as to define a receptacle for
10 receiving a golf ball and which prevents motion thereof in a direction parallel to the striking face of the club head while the ball is retained in said receptacle. The receptacle is ideally provided with an open side thus allowing the ball to be released from said receptacle to fall under gravity in front of or behind the club head depending on the orientation of said receptacle and its open side.

15

In a yet further aspect of the invention there is provided a training method to improve a golf club swing using a golf club with a means for the retention of a golf ball in the golf club head, said golf ball releasable from the golf club head during the swing of the club and wherein said training method involves the steps of placing a golf ball in
20 a retained position in the golf club head, performing a swing with the golf club head and as the swing is performed monitoring the path and speed of the golf ball released from the golf club head during the swing.

BRIEF DESCRIPTION OF THE DRAWINGS

The understanding of the invention is now enhanced by the following specific description in which reference is made to the accompanying diagrams wherein:

5 Figure 1 shows a perspective view of a putter head according to one embodiment of the invention;

Figure 2a to 2b show plan views of modified putter head constructions falling within the scope of the invention;

10

Figures 2c to 2d show a plan view of an attachment according to a modified aspect of the invention as attached to a blade putter head; and

Figures 3 to 5 show perspective views of the mode of operation of the putter as
15 a training device.

DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

The detailed description set forth below in connection with the appended drawings is intended as a description of presently-preferred embodiments of the
20 invention and is not intended to represent the only forms in which the present invention may be constructed and/or utilized. The description sets forth the functions and the sequence of steps for constructing and operating the invention in connection with the illustrated embodiments. However, it is to be understood that the same or equivalent

functions and sequences may be accomplished by different embodiments that are also intended to be encompassed within the spirit and scope of the invention.

Referring firstly to Figure 1 there is shown a putter head 2 provided with a
5 striking face 4, side faces 6, 8 and a rear face 10 which in general define a central
body 12 of the putter head 2. A recess in the form of an aperture 14 is provided within
the body 12 and extends throughout the entire thickness thereof. It will be appreciated
that although the aperture 14 is substantially symmetrically disposed within the body 12
of the putter head 2 about both a lateral axis 16 and a longitudinal axis 18, the precise
10 disposition of the centre of the aperture may be moved within the body 12 so as to be
offset from either of the said axes 16, 18 according to choice or experimentation
regarding the position and size of the sweet spot indicated generally at 14 on the
striking face 4. It will further be appreciated that altering the location of the
aperture 14 alters the dynamic and vibrational characteristics of the putter head, and
15 such characteristics can be further altered by providing a toe weight 20 and/or a heel
weight 22 in the toe or heel portions 24, 26 respectively of the putter head 2.
Henceforth, it will be understood that a large number of modifications and variations
may be made to the putter head 2 as desired and one such modification is to provide
one or more additional apertures in the golf club head which can operate in the same
20 manner as herein described with respect to the single aperture 14.

The heel region 26 is further provided with a location 28 to which a putter shaft may be connected to allow the putter to be swung by a user. Such a shaft is shown in Figures 3 to 5 at 30. Although the putter head of Figure 1 is shown as a mallet-type putter head, it will be immediately understood that a wide variety of shapes can be employed and indeed that the invention can be adopted in other golf clubs such as for example a driver or golf club "woods." The putter head of Figure 2 is further provided with a channeled region 32 having edges 34, 36 which is set back from the upper surfaces of the toe and heel portions 24, 26. Although this feature is not essential to the invention, a putter provided with such a feature can be aligned with the desired direction of travel of a ball struck by the striking face 4 as shown at 38, as the said channel sides 34, 36 define discreet edges 40, 42 which are substantially parallel with the desired striking direction 38, and perpendicular to the striking face 4.

Referring now to Figures 2a and 2b, alternative configurations of putter head 2 are shown. In Figure 2a, the putter head 50 is provided with a U shaped recess 52 in the rear face of the putter head 2. Correct alignment of the putter can be achieved as a result of the further internal faces 54, 56 which define the recess 52, because said faces define edges in the uppermost surface 58 of the putter head which are both parallel with the desired direction of striking and perpendicular to the striking face 4 in similar manner to the edges 40, 42 described above in relation to Figure 1.

A further putter head 6 is shown in Figure 2 and is provided with an aperture 62, the centre of which is offset from both the lateral axis 62 and the longitudinal axis 64. Alignment means 66, 68 are provided in a similar manner to that described in relation to Figure 1.

5

A primary characteristic of the invention is that said recess in whatever form is preferably of marginally greater relevant dimensions than the diameter of the article to be received therein such as a an article in the form of a conventional golf ball and accordingly such a golf ball can be received in a toleranced manner in said apertures and recess. In the case of the recess 52 the distance between the edges 54, 56 is marginally greater than the diameter of a conventional golf ball, whereas the diameter of the circular apertures 14, 62 are marginally greater than the golf ball diameter. Accordingly, the said apertures and recess prevent significant movement of the golf ball in the direction of the longitudinal axes 18, 64, and in the case of Figure 2a, 59 during the back swing and follow through of the putter stroke. This feature is more fully explained with reference to Figures 3 to 5.

Referring now to Figures 2c and 2d, an alternative embodiment is disclosed in which it can be seen that an attachment 70 is provided with attachment means 72 which ideally does not interfere with the striking face 4 of a putter head 74. This functions in a broadly identical manner to the apertures 14, 62 and recess 52 described in relation to Figures 1, 2a and 2b. In both Figures 2c and 2d, the relevant dimensions of the

attachment 70 are marginally greater than the diameter of a conventional golf ball, in order that such may be received within either the recess 76 defined by a pair of rearward extending limbs 75, 75' in the case of Figure 2c, and by the internal walls 77 of a circular hoop in the case of Figure 2d. The said walls 75, 75', or 77 prevent any
5 significant movement of the golf ball in a direction parallel to the striking face 4 of the putter head during the putting stroke.

Referring now to Figures 3 to 5, a putter head 2 as described in Figure 1 is provided with a shaft 30 which is gripped by a user (not shown) and aligned by said
10 user along a desired direction of striking 38. Such alignment is crucial in accurate putting and is aided by the provision of edges 40, 42 in the upper surface of the putter head 2 which allow a user to ascertain the orientation of the striking face 4 of the putter with the desired striking direction 38. It is to be pointed out the material from which the club head is manufactured may not permit the provision of a channel as described,
15 and accordingly the edges 40, 42 may be replaced by painted lines applied to the upper surface of the club face.

The walls of the recess can also be shaped to further control the retention and selected instant of release of the article during a golf swing. For example, the walls
20 can be straight, convex or concave shaped and in one embodiment the aperture can be provided to selectively receive one of a range of insert sleeves, each having a different

inner wall shaping and thereby allowing the characteristics of the recess to be altered for different training requirements.

During play on a golf course, obviously no marking of the desired striking
5 direction exists and the user has only the alignment edges 40, 42 to aid his alignment of the putter such that the striking face 4 is exactly perpendicular with the imagined desired striking direction.

In order to train using the putter head 2 with one recess therein, a pair of golf
10 balls 80, 82 is provided, the first golf ball 80 being positioned in front of the striking face 4 and the second of the golf balls 82 being disposed within the aperture 14 provided in the putter head 2. The aim of the putting training device of the invention is to ensure both that exact perpendicularity is achieved between the striking face 4 and the desired striking direction 38 during impact between the said striking face 4 and the
15 ball 80, and furthermore to ensure that a correct arc of swing is achieved by a user during every putting stroke.

This is achieved as follows:

20 In Figure 4, the putter head 2 has been drawn back from the ball 80 along a back swing arc 84 to the position shown. It can be seen from the figure that the ball 82 is supported only by the ground 86 on which the training is being conducted and

accordingly as the putter head is rotated about the back swing arc 84 and rises above the ground 86, the ball 82 simply drops from within the aperture 14 under gravity, but is nevertheless confined to travel along the line of the desired striking direction 38, except in opposite fashion. It can be seen from the figure that at the extremity of the back swing of the user, the putter is of such a thickness that the ball 82 is not completely released from within the aperture 14, but is partially retained by the walls of said aperture approximate the lowermost surface of the putter head 2.

It is a common flaw of players who are poor putters to break their wrists during the putting stroke and also to concentrate too specifically on the point of impact as opposed to the arc of swing which gives rise to an accurate direction of strike.

With regard to the first flaw, although not shown in any of the diagrams, the arms and wrists of the player ideally remain rigid throughout the putting stroke, with only the shoulders rotating to effect the stroke, and in this manner a uniform and accurate direction of strike is achieved. The breaking of the wrists during the stroke results in the putter head rising above the ground during the backswing and follow through to greater degree than when the arms and wrists of the player remain rigid. The training device of the present invention allows a poor putter to quickly correct this deficiency because the ball 82 will be released from within the aperture if the wrists of the player break during the stroke, whereas during a correctly executed stroke, the wrists would not break and the putter head would rise above the ground 86 only

gradually and to a lesser degree. It is to be further pointed out that the putter of the present invention may be used as a training device with only a single ball 82, and in such configuration could be used simply to hone the putting stroke of the player by ensuring that the player retains the ball 82 within the aperture 14 at all times during a
5 stroke.

With regard to the second flaw, the training device according to the invention defocuses the mind of the user from the impact between the striking face and the ball, and indeed such impact need not actually occur (as discussed above there is no need to
10 provide an object ball 80 which is to be struck by the putter). This form of training can be invaluable in teaching players to “play through the ball” without concentrating specifically on the impact of the face therewith. In all sports, the mental approach of doing more than is actually required, for example in sprinting where sprinters run towards a point past the line, is unequivocally believed to result in improved
15 performance. Accordingly the training device of the invention accomplishes this.

As the putter head begins its down swing from the position shown in Figure 4 to the position shown in Figure 5, the ball 82 remains trapped within the aperture 14 until such time as the putter head 2 is raised a distance at least equal to the diameter of the
20 golf ball 82 above the ground 86. At this stage, the ball 82 is released from within the aperture 14 and as a result of the angular velocity of the putter head 2 at this time, the ball 82 is imparted with a forward velocity directly proportional to the angular velocity

of the said putter head. It is important to note that as the putter head 2 is returned from the position shown in Figure 4 to the stationary position of Figure 3, the striking face 4 impacts the ball 80 and thus imparts a forward velocity to said ball. On account of this impact, and the fact that the angular velocity of the putter head after impact is generally
5 lower than that at impact, the ball 82 will have imparted thereto a lower velocity than the ball 80, and accordingly will lag somewhat behind the said ball 80.

The putter head described acts as a training device in that it is possible for a user of the putter provided with a putter head 2 to ascertain whether the arc of his
10 follow through as shown at 85 is in the correct plane. If this is the case, then the direction of the velocity imparted to the ball 82 will be identical to that direction in which the ball 80 is already traveling, and ideally both of these said directions will be identical to the desired striking direction 38.

15 A common fault of poor putters of the golf ball is the tendency to drag the putter head toward the body after striking the ball 80, and in such circumstances the putter head 2 would follow a path indicated generally by the dotted line 88. If a player whose arc of swing of the putter head 2 is habitually along an incorrect path such as 88, the fault of that player will be immediately evident on using the training device according
20 to the invention because although the ball 80 may travel at least to some extent along the desired striking direction 38, the secondary ball 82 will be released from within the aperture 14 of the putter head in a direction indicated generally by the dotted line 90.

Such instantaneous appraisal of an incorrect putting arc of swing has heretofore been impossible with currently existing putting training devices.

It will be appreciated that the putter heads shown in Figures 2a and 2c operate in a different manner to the putter heads shown in Figures 1, 2b and 2d in that a marking on the ground 86 along the desired striking direction 38 both in front of the striking surface before and behind the putter head 2 is required. The putter head shown in Figures 2a and 2b is ideally adapted to conform to the arc of swing of a player to the correct theoretical arc 84 in the back swing phase of the putting stroke. Henceforth, a ball disposed within the recesses 52, 76 will travel along the marked desired striking direction 38 away from the putter head when said head reaches the extremity of the back swing, and in the case where an incorrect arc of swing is habitually adopted by a player such as that shown at 88 in Figure 5, the direction of travel of the ball away from the putter head will vie away from marked desired striking direction 38. Accordingly, it is possible to use the putter head shown in Figure 1 in a training method wherein three conventional golf balls are used, two being in the positions shown of golf balls 80, 82 in Figure 3 and a third golf ball (not shown) disposed immediately behind and adjacent the rear face 10 and also directly above a marked line indicating the desired striking direction 38. In such method, both the back swing and the follow through of the stroke of the player can be conformed to the correct theoretical arc of swing denoted by 84 and 85 by ensuring that the second golf ball 82 travels along an identical path to that taken by the ball 80 after impact, and also by ensuring that the

third golf ball moves in a direction of the marked line indicating the desired striking direction 38 but in a reverse manner to the balls 80, 82.

5 A number of additional features may be provided in a putter head having the configurations shown in Figures 1, 2a and 2b. In particular, more than a single aperture 14 may be provided, one being disposed toward the toe 24 and the other being disposed towards the heel 26 of the putter head 2. In such circumstances, a pair of golf balls may be disposed within the two apertures of the putter head which, when in use as a training device, would impart a velocity to both the said golf balls disposed in the said
10 aperture on either side of a desired striking direction 38. Imperfections in the arc of swing of a player would accordingly become evident with even more clarity than would be the case with the putter head 2, and furthermore, such a modified putter head may be of use in assessing the particular orientation of the striking surface at impact and thereafter.

15 It has further been proposed to provide a variety of different insert or plugs which could be inserted in the aperture when the putter is being used in conventional play to provide desired dynamic and vibration characteristics which are suited to the particular player. It has also been proposed to provide a fluted aperture whose diameter varies across the thickness of the putter head, and in particular an increasing
20 diameter of aperture from the top surface of the putter head to the bottom surface thereof would allow an earlier release of the ball 82 therefrom. This may be of advantage in testing the short putting stroke of a player, or may be used in

circumstances where the arc of swing of a player is approximately correct but requires slight fine tuning.

A yet further proposal is to provide an elastomeric ring on the inner surface of
5 the aperture 14 to enable a player using the putter in conventional play to lift a ball from the ground by simply urging the putter head over the ball such that it locates within the aperture and engages the elastomeric ring to be subsequently held thereby.

To enhance the overall aesthetic appearance of the putter head 2, caps may be
10 provided to cover the aperture either on the upper surface thereof and/or on the lower surface. Such caps could be of use in identification purposes or alternatively may be provided with further alignment features to enhance the alignment capabilities of the putter head and the player as a whole.

15 Both caps and any insert or plugs provided within the aperture may be transparent, and indeed the entire putter head may be manufactured of a transparent material.

A yet further insert can be provided for reception in the recess and can be used
20 as a weight. The insert can also include different weighted portions and one or more recesses provided in its uppermost surface such that a user of the putter and insert can alter, typically by rotation, the position of the insert with respect to the club head and

hence alter the weight distribution when disposed within the aperture to provide the putter head with altered dynamic and vibrational characteristics to suit the particular preference of the player. In one embodiment, unwanted movement or rotation of said weight can easily be prevented by a simple locking device such as a grub screw
5 tightenable against the surface of the weight using an allen key inserted through a conveniently disposed aperture in the putter head.

It will be immediately evident to those skilled on the art that a wide variety of modifications and amendment may be made to the invention without exceeding the
10 scope or departing from the spirit thereof.